

## **Earth connection assembly for System „Quicky -soft- 2000“**

Delivery of a “Quicky Soft 2000” system earth bonded construction of welded steel wire mesh mats with eyelets welded right round, wire diameter 5.0 mm and mesh size 10 x 10 cm. Steel wire mesh mats with a tensile strength of  $\geq 450$  N/mm<sup>2</sup>. Tensile strength of the eyelets to be the same as of the wire.

Insertable rods  $\varnothing$  6.0 mm, 450 N/mm<sup>2</sup>,  
Separators  $\varnothing$  5.0 mm, 450 N/mm<sup>2</sup>, 2 each at a distance of 20 cm from the edges and further at a distance of 40 cm, produced to fit exactly for the required inclination of the construction.

All parts are specially aluminium galvanised with a aluminum content of  $\geq 10\%$  and a corrosion resistance of at least 3.000 hour in a salt spray test according to DIN EN 9227-NSS.

Reinforcement according to static requirements, with certification from the Institute for Construction Technology.

Delivery of an erosion protection mat (where required with grass seed embedded) for the front area, for insertion behind the steel wire mesh mat.

Assembly of the component parts according to the manufacturer's assembly instructions.

Billing by sqm of elevated surface.

Supplier:

**HOY Geokunststoffe GmbH**  
**Zum Wiesengrund 5**  
**01723 Kesselsdorf**

**Tel.: 035204/70110**

**Fax.: 035204/70120**

**E-Mail: [info@hoy-geotextilien.de](mailto:info@hoy-geotextilien.de)**